

TECHNICAL INFORMATION



SLABLAYER

Ready-to-use Slablayer Product Data Sheet

Blue Circle Slablayer is a cement-based material containing specially selected sand and cement for use under patio paving slabs. It is easy to use and requires

no mixing and gradually over a period of time develops hardness to support the slabs.

USES

Blue Circle Slablayer can be used under most types of patio slabs to provide a level surface.

DESCRIPTION


Blue Circle Slablayer consists of cement and selected aggregates.

PACKAGING

Blue Circle Slablayer is packed in tear-resistant weatherproof 20 kg plastic packaging.

CLEANING

All equipment should be cleaned with water. Do not flush down drains.



SITWORK

For best results follow these instructions:

1. Prepare the area to the required depth. Remove turf and any other material which will interfere with the surface being flat and level.
2. Place Blue Circle Slablayer to the required depth (optimum 25 mm), and rake level. Sprinkle with water using a fine rose until the Blue Circle Slablayer is wet through and rake level again.
3. Place the paving slabs ensuring they are level and flat. (If slabs are dry, dampen the underside of the slab before laying onto the Blue Circle Slablayer).
4. Ensure that no cement material remains on the surface of the slabs as this will result in staining.
5. Point the slabs using a suitable mortar.

COVERAGE

This will depend on the depth of material used but as a guide three 440 mm x 440 mm paving slabs can be laid with one 20 kg bag when the Blue Circle Slablayer is used at 25 mm thick. For detailed calculations go to www./tarmac-bluecircle.co.uk/product/slablayer-trade/

AVAILABILITY

Blue Circle Slablayer is available throughout the United Kingdom from Tarmac Cement stockists.

TECHNICAL SUPPORT

Further information and advice on Blue Circle Slablayer and the full range of Tarmac Cement products can be obtained through the contacts listed below.

STORAGE

This product may be stored in either indoor or outdoor conditions. Information on the maximum storage period can be found on the bag. Blue Circle Slablayer is a cement-based material and should be handled and stored with care.

CONDITIONS OF USE

- Blue Circle Slablayer may only be used for bedding and grounding slabs
- Blue Circle Slablayer may not be used for general concreting, screeds, mortar, grout and render

- If a particular compressive strength is required, Blue Circle Slablayer should not be used
- It is essential that Blue Circle Slablayer is prevented from drying-out too rapidly. Generally, adequate curing is achieved by protecting the material from adverse weather conditions until fully hardened and thereafter allowing to dry slowly over several days
- The final quality of the job will depend upon the operative having the required skills and a familiarity with the material and its application methods
- Normal site practice to the relevant British and European Standards should always apply. Tarmac Cement cannot be held responsible where workmanship has not been carried out in accordance with good practice
- Manual handling should comply with *The Manual Handling Operations Regulations 1992*.

HEALTH AND SAFETY

Product contains cement. Contact between cement powder and body fluids (eg, sweat and eye fluids) may cause irritation, dermatitis or burns. For further information, including control of soluble hexavalent chromium, refer to the appropriate Tarmac Cement Health and Safety Information Sheet.



For further information

Technical helpdesk

Tel: 0845 812 6232

E-mail info-cement@tarmac.com

Customer services & sales

Tel: 0845 812 6300

E-mail customerservice@tarmac.com

Tarmac' and the 'circle logo' are registered trademarks. ©2015 Tarmac Trading Limited

The information in this data sheet is accurate at the time of printing, but Tarmac reserves the right to amend details as part of its product development programme. The information given in this technical data sheet is based on our current knowledge and is intended to provide general notes on our products and their uses. Tarmac endeavour to ensure that the information given is accurate, but accept no liability for its use or its suitability for particular application because of the product being used by the third party without our supervision. Any existing intellectual property right must be observed.