

Tarmac Cement National Laboratory

Yelsway Lane Waterhouses Staffordshire ST10 3AZ

25.05.2023

Composition of Ground Granulated Blastfurnace Slag

Tudela EN 15167-1 GGBS (0099/CPR/B34/0001)

Based on the March 2023 monthly composite sample: 0947

Property			Value	BS EN 15167-1 Limit
Magnesia	MgO	%	7.56	≤ 18.0%
Sulfate	SO₃	%	0.10	≤ 2.5%
Sulfide	S2 ⁻	%	0.63	≤ 2.0%
Chloride	CI-	%	0.02	≤ 0.1%
Alkalis	Na₂Oeq	%	0.59	-
Alumina	Al ₂ O ₃	%	11.41	≤ 14%*
Fineness	SSA	m²/kg	491	≥ 275 m²/kg
7 Day Activity Index – February Sar	nple	%	49	>40%
28 Day Activity Index – February Sa	ample	%	78	>65%
Declared Mean Alkali Content	Na₂Oeq	%	0.70	-
Declared Maximum Chloride Content	Cl-	%	0.05	-

^{*}Upper limit in BS 8500 for use in '+SR' combinations

For and on behalf of Tarmac Cement:

S. Chudley

Simon Chudley

National Commercial Technical Manager Tarmac Cement

TARMAC.COM



Conformity of Ground Granulated Blast Furnace Slag to BS 8500-2: Annex A Tudela EN 15167-1 GGBS (0099/CPR/B34/0001)

Based on the composite samples for the month of: March 2023

Constituent	Source
EN 15167-1 GGBS	Tudela
EN 197-1 CEM I	Aberthaw

The results of compressive strength testing (in accordance with BS EN 196-1) of a 50:50 blend of CEM I with GGBS were:

7 Day Strength (MPa)	29.7
28 Day Strength (MPa)	51.8

Based on equivalent results obtained for the last **12** months, the permitted proportions of combinations conforming to the requirements of Annex A of BS 8500-2 are:

Strength Class of Combination	GGBS Content (%)	
	Min	Max
32,5L	50	80
42,5L	18	71
52,5L	6	33

BS 8500-2 Combination	GGBS Content (%)	
Designation	Min	Max
CIIS	6	35
CIIIA	36	65
CIIIB	66	80

For and on behalf of Tarmac Cement:

Simon Chudley

National Commercial Technical Manager Tarmac Cement TARMAC.COM



Conformity of Ground Granulated Blast Furnace Slag to BS 8500-2: Annex A Tudela EN 15167-1 GGBS (0099/CPR/B34/0001)

Based on the composite samples for the month of: March 2023

Constituent	Source
EN 15167-1 GGBS	Tudela
EN 197-1 CEM I	Cauldon

The results of compressive strength testing (in accordance with BS EN 196-1) of a 50:50 blend of CEM I with GGBS were:

7 Day Strength (MPa)	30.1
28 Day Strength (MPa)	51.5

Based on equivalent results obtained for the last **12** months, the permitted proportions of combinations conforming to the requirements of Annex A of BS 8500-2 are:

Strength Class of Combination	GGBS Content (%)	
	Min	Max
32,5L	65	80
42,5L	6	75
52,5L	6	33

BS 8500-2 Combination	GGBS Content (%)	
Designation	Min	Max
CIIS	6	35
CIIIA	36	65
CIIIB	66	80

For and on behalf of Tarmac Cement:

Simon Chudley

National Commercial Technical Manager Tarmac Cement TARMAC.COM



Conformity of Ground Granulated Blast Furnace Slag to BS 8500-2: Annex A Tudela EN 15167-1 GGBS (0099/CPR/B34/0001)

Based on the composite samples for the month of: March 2023

Constituent	Source
EN 15167-1 GGBS	Tudela
EN 197-1 CEM I	Dunbar

The results of compressive strength testing (in accordance with BS EN 196-1) of a 50:50 blend of CEM I with GGBS were:

7 Day Strength (MPa)	22.6
28 Day Strength (MPa)	50.0

Based on equivalent results obtained for the last **12** months, the permitted proportions of combinations conforming to the requirements of Annex A of BS 8500-2 are:

Strength Class of Combination	GGBS Content (%)	
	Min	Max
32,5L	50	80
42,5L	29	50
52,5L	6	41

BS 8500-2 Combination	GGBS Content (%)	
Designation	Min	Max
CIIS	6	35
CIIIA	36	65
CIIIB	66	80

For and on behalf of Tarmac Cement:

Simon Chudley

National Commercial Technical Manager Tarmac Cement TARMAC.COM

AKWAC.COW



Conformity of Ground Granulated Blast Furnace Slag to BS 8500-2: Annex A Tudela EN 15167-1 GGBS (0099/CPR/B34/0001)

Based on the composite samples for the month of: March 2023

Constituent	Source
EN 15167-1 GGBS	Tudela
EN 197-1 CEM I	Hope

The results of compressive strength testing (in accordance with BS EN 196-1) of a 50:50 blend of CEM I with GGBS were:

7 Day Strength (MPa)	29.4
28 Day Strength (MPa)	54.4

Based on equivalent results obtained for the last **12** months, the permitted proportions of combinations conforming to the requirements of Annex A of BS 8500-2 are:

Strength Class of Combination	GGBS Content (%)	
	Min	Max
32,5L	58	80
42,5L	6	71
52,5L	6	15

BS 8500-2 Combination	GGBS Content (%)	
Designation	Min	Max
CIIS	6	35
CIIIA	36	65
CIIIB	66	80

For and on behalf of Tarmac Cement:

Simon Chudley

National Commercial Technical Manager Tarmac Cement TARMAC.COM



Conformity of Ground Granulated Blast Furnace Slag to BS 8500-2: Annex A Tudela EN 15167-1 GGBS (0099/CPR/B34/0001)

Based on the composite samples for the month of: March 2023

Constituent	Source
EN 15167-1 GGBS	Tudela
EN 197-1 CEM I	Limerick

The results of compressive strength testing (in accordance with BS EN 196-1) of a 50:50 blend of CEM I with GGBS were:

7 Day Strength (MPa)	27.2
28 Day Strength (MPa)	50.8

Based on equivalent results obtained for the last **12** months, the permitted proportions of combinations conforming to the requirements of Annex A of BS 8500-2 are:

Strength Class of Combination	GGBS Content (%)	
	Min	Max
32,5L	50	80
42,5L	6	69
52,5L	6	27

BS 8500-2 Combination	GGBS Content (%)	
Designation	Min	Max
CIIS	6	35
CIIIA	36	65
CIIIB	66	80

For and on behalf of Tarmac Cement:

Simon Chudley

National Commercial Technical Manager Tarmac Cement TARMAC.COM

Tarmac Cement and Lime Limited Registered in England and Wales. Company No. 66558

Registered address: T3 Trinity Park, Bickenhill Lane, Birmingham, B37 7ES



Conformity of Ground Granulated Blast Furnace Slag to BS 8500-2: Annex A Tudela EN 15167-1 GGBS (0099/CPR/B34/0001)

Based on the composite samples for the month of: March 2023

Constituent	Source
EN 15167-1 GGBS	Tudela
EN 197-1 CEM I	Mannock

The results of compressive strength testing (in accordance with BS EN 196-1) of a 50:50 blend of CEM I with GGBS were:

7 Day Strength (MPa)	31.4
28 Day Strength (MPa)	54.3

Based on equivalent results obtained for the last **12** months, the permitted proportions of combinations conforming to the requirements of Annex A of BS 8500-2 are:

Strength Class of Combination	GGBS Content (%)	
	Min	Max
32,5L	58	80
42,5L	6	72
52,5L	6	37

BS 8500-2 Combination	GGBS Content (%)	
Designation	Min	Max
CIIS	6	35
CIIIA	36	65
CIIIB	66	80

For and on behalf of Tarmac Cement:

Simon Chudley

National Commercial Technical Manager Tarmac Cement TARMAC.COM



Conformity of Ground Granulated Blast Furnace Slag to BS 8500-2: Annex A Tudela EN 15167-1 GGBS (0099/CPR/B34/0001)

Based on the composite samples for the month of: March 2023

Constituent	Source
EN 15167-1 GGBS	Tudela
EN 197-1 CEM I	Platin

The results of compressive strength testing (in accordance with BS EN 196-1) of a 50:50 blend of CEM I with GGBS were:

7 Day Strength (MPa)	28.1
28 Day Strength (MPa)	52.0

Based on equivalent results obtained for the last **12** months, the permitted proportions of combinations conforming to the requirements of Annex A of BS 8500-2 are:

Strength Class of Combination	GGBS Content (%)	
	Min	Max
32,5L	48	80
42,5L	6	66
52,5L	6	34

BS 8500-2 Combination	GGBS Content (%)	
Designation	Min	Max
CIIS	6	35
CIIIA	36	65
CIIIB	66	80

For and on behalf of Tarmac Cement:

Simon Chudley

National Commercial Technical Manager Tarmac Cement TARMAC.COM



Conformity of Ground Granulated Blast Furnace Slag to BS 8500-2: Annex A Tudela EN 15167-1 GGBS (0099/CPR/B34/0001)

Based on the composite samples for the month of: March 2023

Constituent	Source
EN 15167-1 GGBS	Tudela
EN 197-1 CEM I	Tunstead

The results of compressive strength testing (in accordance with BS EN 196-1) of a 50:50 blend of CEM I with GGBS were:

7 Day Strength (MPa)	27.0
28 Day Strength (MPa)	55.9

Based on equivalent results obtained for the last **12** months, the permitted proportions of combinations conforming to the requirements of Annex A of BS 8500-2 are:

Strength Class of Combination	GGBS Content (%)	
	Min	Max
32,5L	58	80
42,5L	6	69
52,5L	6	29

BS 8500-2 Combination	GGBS Content (%)	
Designation	Min	Max
CIIS	6	35
CIIIA	36	65
CIIIB	66	80

For and on behalf of Tarmac Cement:

Simon Chudley

National Commercial Technical Manager Tarmac Cement TARMAC.COM